

Kiilto Pro Hospitalssprit 70%

Replaces date: 15/06/2022

Revision date: 19/12/2022 Version: 2.0.1

HILTO

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name:	Kiilto Pro Hospitalssprit 70%
Group name:	Disinfection products
Synonyms:	Hospitalssprit 70% Plum Hospitalssprit 70%

Unique Formula Identifier (UFI): 03UX-6J97-U002-0937

Article no

Article no	Description
201096	1000 ml
201098	5000 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses:	Biocide. Use biocides safely. Always read the label and product information before use.
	Surface Disinfection. PT 2 Disinfectants and algaecides not intended for direct application to humans or animals.
	Solvent.
	Cleaning agent Cleaner
Inadvisable uses:	Hand disinfection. By prolonged contact, the product may dry the skin.
1.3. Details of the supp	lier of the safety data sheet
Supplier	
Company:	KiiltoClean A/S
Address:	Frederik Plums Vej 2
Zip code:	5610
City:	Assens

1	
City:	Assens
Country:	DENMARK
E-mail:	info.dk@kiilto.com
Phone:	+45 64712112
Fax:	+45 64712125
Homepage:	www.kiilto.dk

1.4. Emergency Telephone Number

Members of the public: 111 (NHS 111 (Scotland: NHS 24)). The emergency telephone is open 24 hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP-classification:	Flam. Liq. 3;H226 Eye Irrit. 2;H319
---------------------	-------------------------------------

Most serious harmful effects: Flammable liquid and vapour. Causes serious eye irritation.

Kiilto Pro Hospitalssprit 70%

Replaces date: 15/06/2022

2.2. Label elements



Revision date: 19/12/2022 Version: 2.0.1

Pictograms



Signal word:	Warning
Hazard Statements	
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
Precautionary statements	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container as hazardous waste. Rinsed container can be sorted as plastic.
Supplemental information	

Use: Surface disinfection.

Type of formulation: Liquid Active substances: 567 g/kg ethanol (CAS no. 64-17-5) and 60 g/kg propan-2-ol (CAS no. 67-63-0). Dosage: Apply solution onto surface or cloth/wipe and keep surface moist according to the stated contact time. Wipe the surface repeatedly. Allow the surface to air dry.

2.3. Other hazards

The product does not contain any PBT or vPvB substances.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	CAS No./ EC No./ REACH Reg. No.	Concentration	Notes	CLP-classification
Ethanol	64-17-5 200-578-6 01-2119457610-43-xxxx	50 - 70 %	13, 15	Flam. Liq. 2;H225 Eye Irrit. 2;H319 C ≥ 50%: Eye Irrit. 2;H319
propan-2-ol	67-63-0 200-661-7 01-2119457558-25-xxxx	5 - 10 %	13	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336

Please see section 16 for the full text of H- / EUH-phrases.

13 = The substance has a national exposure limit.

15 = REACH-registered with a different classification than in Regulation 1272/2008 Appendix VI.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:	Seek fresh air. Seek medical advice in case of persistent discomfort.			
Ingestion:	Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medica advice in case of discomfort.	I		
Skin contact:	Remove contaminated clothing. Wash the skin with water. Seek medical advice in cas	e of		
Copyright © 1995 - 2022 DGOffice B.V., Made with CHESS in www.DGDoc.net 2 / 12				



Replaces date: 15/06/2022

Revision date: 19/12/2022 Version: 2.0.1

	persistent discomfort.
Eye contact:	Flush immediately with water (preferably using eye wash equipment) for at least 5 minutes. Open eye wide. Remove any contact lenses. Seek medical advice.
General:	When obtaining medical advice, show the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Direct contact: Irritating to eyes. Causes a burning sensation and tearing. Degreases and dries the skin. Repeated exposure may cause skin dryness or cracking. The product releases organic solvent vapours which may cause lethargy and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms. No special immediate treatment required.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:	Extinguish with powder, foam, carbon dioxide or water mist. Use water or water mist to cool non-ignited stock.
Unsuitable extinguishing media:	Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released. Among other: Carbon monoxide and carbon dioxide.

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures. Vapours are heavier than air and may spread near ground to sources of ignition.

5.3. Advice for firefighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air. Wear Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Stop leak if this can be done without risk. Provide adequate ventilation. Smoking and naked flames prohibited. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Take precautionary measures against static discharges. Use spark-free tools and explosion proof equipment. Wear safety goggles if there is a risk of eye splash.

For emergency responders: In addition to the above: Normal protective clothing equivalent to EN 469 is recommended.

6.2. Environmental precautions

Avoid unnecessary release to the environment.

6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent, non-combustible material and transfer to suitable waste containers. Wipe up minor spills with a cloth. Rinse with water. Provide good ventilation.

6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.



Kiilto Pro Hospitalssprit 70%

Replaces date: 15/06/2022

Revision date: 19/12/2022 Version: 2.0.1

Other Information:

Minor spillage from single containers is not expected to cause accumulation of vapours in explosive concentrations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use the product under well-ventilated conditions. Do not eat, drink or smoke during work. Wash hands before breaks, before using restroom facilities, and at the end of work. Running water and eye wash equipment must be available. Smoking and naked flames prohibited. Take precautionary measures against static discharges. Use spark-free tools and explosion proof equipment. A workplace assessment must be conducted to ensure that employees are not exposed to effects that may involve a risk during pregnancy.

7.2. Conditions for safe storage, including any incompatibilities

Store safely and keep out of reach of children. Keep in tightly closed original packaging. Storage temperature: 0-30 °C. The vapours are heavier than air and will spread along the floor. The vapours may form explosive mixtures with air.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit

Substance name	Time period	ppm	mg/m³	fiber/cm3	Remarks	Comments
ethanol	8h	1000	1920			
propan-2-ol	15m	500	1250			
propan-2-ol	8h	400	999			

Measuring methods:

Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.

Legal basis:

EH40/2005 Workplace exposure limits. Last amended January 2020.

PNEC

Ethanol, cas-no 64-17-5				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC aqua (intermittent releases)	2,75 mg/l			
water)	0,79 mg/l			
PNEC aqua (intermittent releases)	2,75 mg/l			
PNEC sediment (freshwater)	3,6 mg/kg			
(water)	2,9 mg/kg			
PNEC STP (wastewater- treatment facilities)	580 mg/l			
PNEC soil	0,63 mg/kg			
PNEC aqua (freshwater)	0,96 mg/l			

Kiilto Pro Hospitalssprit 70%

Replaces date: 15/06/2022

Revision date: 19/12/2022 Version: 2.0.1

KiiLTO

propan-2-ol, cas-no 67-63	propan-2-ol, cas-no 67-63-0								
Exposure	Value	Assessment Factor	Extrapolation Method	Note					
PNEC aqua (freshwater)	140,9 mg/l								
PNEC aqua (marine water)	140,9 mg/l								
PNEC aqua (intermittent releases)									
PNEC STP (wastewater- treatment facilities)	2251 mg/l								
PNEC soil	552 mg/kg dw								
PNEC soil	28 mg/kg								

DNEL - workers

Ethanol, cas-no 64-17-5 Main Impact Exposure Value Assessment Factor **Dose Descriptor** Note Parameter Inhalation DNEL (acute/short-term 1900 mg/m³ exposure - local effects) Dermal DNEL (longterm exposure -343 mg/kg bw/day systemic effects) Inhalation DNEL (long-term exposure 950 mg/m³ - systemic effects) propan-2-ol, cas-no 67-63-0 Main Impact Exposure Value Assessment Factor **Dose Descriptor** Note Parameter Dermal DNEL (longterm exposure -888 mg/kg bw/day systemic effects) Inhalation DNEL (long-term exposure 500 mg/m³ - systemic effects)

DNEL - general population

Ethanol, cas-no 64-1	7-5							
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note			
Dermal DNEL (long- term exposure - systemic effects)	206 mg/kg bw/day							
Oral DNEL (long- term exposure - systemic effects)	87 mg/kg bw/day							
Inhalation DNEL (long-term exposure - systemic effects)	114 mg/m³							
Inhalation DNEL (acute/short-term exposure - local effects)	950 mg/m³							
propan-2-ol, cas-no 67-63-0								
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note			

Replaces date: 15/06/2022

Revision date: 19/12/2022 Version: 2.0.1

KiiLTO

			version. 2.0.1
Dermal DNEL (long- term exposure - systemic effects)	319 mg/kg bw/day		
Oral DNEL (long- term exposure - systemic effects)	26 mg/kg bw/day		
Inhalation DNEL (long-term exposure - systemic effects)	89 mg/m³		

8.2. Exposure controls

Appropriate engineering controls:	Wear the personal protective equipment specified below.
Personal protective equipment, eye/face protection:	Not required for normal expected usage. Wear safety goggles if there is a risk of eye splash. Eye protection must conform to EN 166.
Personal protective equipment, skin protection:	Ordinary workwear.
Personal protective equipment, hand protection:	Wear gloves. Type of material: Nitrile rubber/ Butyl rubber. Breakthrough time has not been determined for the product. Change gloves often. Gloves must conform to EN 374.
Personal protective equipment, respiratory protection:	Normally not required. In case of insufficient ventilation, wear respiratory protective equipment. Filter type: A. Respiratory protection must conform to one of the following standards: EN 136/140/145.
Environmental exposure controls:	Ensure compliance with local regulations for emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Parameter		Value/unit			
State	Liquid				
Colour	Clear				
Odour	Alcohol				
Solubility	Miscible with the followir	ng: Water. Alcohols.			
Parameter	Value/unit	Remarks			
Odour threshold	No data				
Melting point	No data				
Freezing point	No data				
Initial boiling point and boiling range	~ 80 °C				
Flammability (solid, gas)	No data				
Flammability limits	No data				
Explosion limits	3.3 - 19 vol%	Ethanol			
Flash Point	23 °C	ASTM D 3278			
Auto-ignition temperature	No data				
Decomposition temperature	No data				
pH (solution for use)	7 - 9	As supplied (use undiluted).			
pH (concentrate)	7 - 9	As supplied			
Kinematic viscosity	No data				
Viscosity	No data				
Partition coefficient n-octonol/water	No data				
Vapour pressure	No data				
Density	0,881 g/cm ³				
Relative density	No data				

Copyright © 1995 - 2022 DGOffice B.V., Made with CHESS in www.DGDoc.net



Kiilto Pro Hospitalssprit 70%

Replaces date: 15/06/2022

Vapour density	> 1	Reference gas: Air = 1
Relative density (sat. air)	No data	
Particle characteristics	No data	

9.2. Other information

Parameter	Value/unit	Remarks
Explosive properties		The product is not explosive, but may form explosive mixtures with air.
Oxidising properties		Non-oxidising.

Other Information:

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with the following: Strong oxidisers.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

None.

10.3. Possibility of hazardous reactions

Product vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Avoid heating and contact with ignition sources.

10.5. Incompatible materials

Strong oxidisers.

10.6. Hazardous decomposition products

None, if stored at the recommended storage conditions. Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released. Among other: Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - oral

Ethanol, cas-no 64-17-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source		
Rat	LD50		> 2000 mg/kg		OECD TG 401	Supplier		
propan-2-ol, cas-no 67-63-0								
Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source		
Rat	LD50		> 2000 mg/kg			Supplier		

Ingestion may cause discomfort. Ingestion may cause similar symptoms to those resulting from inhalation. The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Acute toxicity - dermal

Ethanol, cas-no 64-17-5								
Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source		
Rabbit	LD50		> 2000 mg/kg		OECD TG 402	Supplier		

propan-2-ol, cas-no 67-63-0

Copyright © 1995 - 2022 DGOffice B.V., Made with CHESS in www.DGDoc.net



Revision date: 19/12/2022

Safety Data Sheet

Kiilto Pro Hospitalssprit 70%

Replaces date: 15/06/2022

						Version: 2.0.7	1
Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source	
Rabbit	LD50		> 2000 mg/kg			Supplier	

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Acute toxicity - inhalation

Ethanol, cas-no 64-17-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source		
Mouse		4 h	> 20 mg/l			Supplier		
propan-2-ol, cas-no 67-63-0								
Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source		
Rat	LC50	8 h	> 20 mg/l			Supplier		

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Skin corrosion/irritation

Ethanol, cas-no 64-17-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source		
Rabbit	Irritation				OECD TG 404	Supplier		
propan-2-ol, cas-no 67-63-0								
Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source		
Rabbit				Non-irritating		Supplier		

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Serious eye damage/eye irritation

Ethanol, cas-no 64-17-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit				Moderate eye irritation	OECD TG 405	Supplier
propan-2-ol, ca	as-no 67-63-0					
Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit				Irritating		Supplier

Direct contact: Irritating to eyes. Causes a burning sensation and tearing.

Respiratory sensitisation or skin sensitisation

Ethanol, cas-no 64-17-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Guinea Pig				Not sensitizing	OECD TG 406	Supplier
propan-2-ol, c	as-no 67-63-0					
Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Guinea Pig	Buehler-Test			Not sensitizing		Supplier

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Copyright © 1995 - 2022 DGOffice B.V., Made with CHESS in www.DGDoc.net 8 /				
Aspiration hazard:	The product does not have to be classified. Test data cannot be obtained for technical	I		
Repeated STOT exposure:	The product does not have to be classified. Test data are not available.			
Single STOT exposure:	The product does not have to be classified. Test data are not available.			
Reproductive toxicity:	The product does not have to be classified. Test data are not available.			
Carcinogenic properties:	The product does not have to be classified. Test data are not available.			
Germ cell mutagenicity:	The product does not have to be classified. Test data are not available.			



Replaces date: 15/06/2022

Revision date: 19/12/2022 Version: 2.0.1

11.2. Information on other hazards

Endocrine disrupting properties:	None known.

reasons.

Degreases and dries the skin. Repeated exposure may cause skin dryness or cracking. The product releases organic solvent vapours which may cause lethargy and dizziness. The product does not have to be classified. Test data are not available.

SECTION 12: Ecological information

12.1. Toxicity

Ethanol, cas-no 64-17-5

Other toxicological effects:

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Fish	Leuciscus idus melanotus	48 h		> 100 mg/l			Supplier
Algea or other acquatic plants				5000 mg/l			Supplier
Crustacea	Daphnia magna	24 h		> 100 mg/l			Supplier
Bacteria	Pseudomonas putida	16 h		6500 mg/l			Supplier

propan-2-ol, cas-no 67-63-0

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Fish	Leuciscus idus melanotus	48 h	LC50	> 100 mg/l			Supplier
Crustacea	Daphnia magna	48 h	EC50	> 100 mg/l			Supplier
Algea or other acquatic plants	Scenedesmus subspicatus	72 h		> 100 mg/l			Supplier

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

12.2. Persistence and degradability

Readily biodegradable.

12.3. Bioaccumulative potential

No bioaccumulation expected.

12.4. Mobility in soil

Soluble in water. The product contains organic solvents which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

None known.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

Copyright © 1995 - 2022 DGOffice B.V., Made with CHESS in www.DGDoc.net



Replaces date: 15/06/2022

Revision date: 19/12/2022 Version: 2.0.1

13.1. Waste treatment methods

Avoid unnecessary release to the environment. Collect spills and waste in closed, leak-proof containers for disposal at the local hazardous waste site.

Wiping cloths with organic solvents: EWC code: 15 02 02 Absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances.

Empty, cleansed packaging should be disposed of for recycling. Uncleansed packaging is to be disposed of via the local wasteremoval scheme.

Category of waste:

Depending on the end use:

07 07 04* other organic solvents, washing liquids and mother liquors

16 03 05* organic wastes containing hazardous substances

18 02 05* chemicals consisting of or containing hazardous substances

SECTION 14: Transport information

Land transport (ADR/RID)			
14.1. UN number or ID number:	1987	14.4. Packing group:	
14.2. UN proper shipping name:	ALCOHOLS, N.O.S. (Ethanol) (propan-2-ol)	14.5. Environmental hazards:	The product should not be labelled as an environmental hazard (symbol: fish and tree).
14.3. Transport hazard class(es):	3		,
Hazard label(s):	3		
Hazard identification number:	30	Tunnel restriction code:	D/E
Inland water ways transport	(ADN)		
14.1. UN number or ID number:	1987	14.4. Packing group:	
14.2. UN proper shipping name:	ALCOHOLS, N.O.S. (Ethanol) (propan-2-ol)	14.5. Environmental hazards:	The product should not be labelled as an environmental hazard (symbol: fish and tree).
14.3. Transport hazard class(es):	3		
Hazard label(s):	3		
Transport in tank vessels:	Not applicable.	Other Information:	-
Sea transport (IMDG)			
14.1. UN number or ID number:	1987	14.4. Packing group:	
14.2. UN proper shipping name:	ALCOHOLS, N.O.S. (Ethanol) (propan-2-ol)	14.5. Environmental hazards:	The product is not a Marine Pollutant (MP).
14.3. Transport hazard class(es):	3	Environmental Hazardous Substance Name(s):	-
11			
Hazard label(s):	3		
Hazard label(s): EmS:	3 F-E, S-D	IMDG Code segregation group:	- None -
	F-E, S-D		- None -
EmS:	F-E, S-D A-DGR)		- None - III
EmS: Air transport (ICAO-TI / IATA	F-E, S-D A-DGR)	group:	
EmS: Air transport (ICAO-TI / IATA 14.1. UN number or ID number: 14.2. UN proper shipping	F-E, S-D A-DGR) 1987 ALCOHOLS, N.O.S. (Ethanol)	group: 14.4. Packing group: 14.5. Environmental	



Kiilto Pro Hospitalssprit 70%

Replaces date: 15/06/2022

Revision date: 19/12/2022 Version: 2.0.1

14.6. Special precautions for user

None.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

Other Information:

May be transported in limited quantities if placed in outer packaging according to ADR 3.4, when max. 5 liter/inner packaging and max. 30 kg total gross mass. Shrink- or stretch wrapped trays may be used and shall not exceed 20 kg total gross mass/tray. May be transported in limited quantities if placed in outer packaging according to IMDG 3.4, when max. 5 liter/inner packaging and max. 30 kg total gross mass. Shrink- or stretch wrapped trays may be used and shall not exceed 20 kg total gross mass. Shrink- or stretch wrapped trays may be used and shall not exceed 20 kg total gross mass. Shrink- or stretch wrapped trays may be used and shall not exceed 20 kg total gross mass/tray.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special Provisions:	REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).
	Regulation (EU) of the European Parliament and of the Council concerning the making available on the market and use of biocidal products. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
	COMMISSION REGULATION (EU) 2020/878 (SDS). Directive 2012/18/EU (Seveso), P5c FLAMMABLE LIQUIDS: Column 2: 5000 t, Column 3: 50000 t.
	European Agreement concerning the International Carriage of Dangerous Goods by Road. Council Directive (EC) on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.
	Council Directive (EC) on the protection of young people at work. Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product.

15.2. Chemical Safety Assessment

Other Information:

Chemical safety assessment has not been performed.

SECTION 16: Other information

Version history and indication of changes

Version	Revision date	Responsible	Changes
2.0.1	19/12/2022	KiiltoClean A/S (SKP)	3.2, 15, 16
2.0.0	15/06/2022	KiiltoClean A/S (SKP)	2020/878, UFI + Name
1.0.0	25/03/2019	Plum A/S (SKP)	New
Abbreviations:	DNEL: Derived No Effect PNEC: Predicted No Effect STOT: Specific Target O PBT: Persistent, Bioaccu vPvB: Very Persistent ar	ect Concentration Irgan Toxicity Imulative and Toxic	
Other Information:	Batch number and expiration date appears from the packaging. Additional information can be obtained by contacting info.dk@kiilto.com or by telephone +45 6471 2112.		
Training advice:	A thorough knowledge of this safety data sheet should be a prerequisite condition.		
Date:	19/12/2022		



Kiilto Pro Hospitalssprit 70%

Replaces date: 15/06/2022

Revision date: 19/12/2022 Version: 2.0.1

Classification method:	Calculation based on the hazards of the known components. Test data.
List of relevant H-statements	6
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Product type:	PT 2 Disinfectants and algaecides not intended for direct application to humans or animals. Surface Disinfection.
SDS is prepared by	
Company:	KiiltoClean A/S
Address:	Frederik Plums Vej 2
Zip code:	5610
City:	Assens
Country:	DENMARK
E-mail:	info.dk@kiilto.com
Phone:	+45 64712112
Fax:	+45 64712125
Homepage:	www.kiilto.dk
Country:	GB